# FOR FINE SOUND ALL AROUND



standardized on audiotape audiodiscs audiofilm



... because "No other sound recording media have been found to meet our exacting requirements for consistent, uniform quality."

In professional circles Bob Fine is a name to reckon with. His studio, one of the country's largest and best equipped, cuts the masters for over half the records released each year by independent record manufacturers. Movies distributed throughout the world, filmed TV broadcasts, transcribed radio broadcasts, and advertising transcriptions are recorded here at Fine Sound, Inc., on Audio products.

Every inch of tape used here is Audiotape. Every disc cut is an Audiodisc. And now, Fine Sound is standardizing on Audiofilm. That's proof of the consistent, uniform quality of all Audio products: these Fine Sound craftsmen use them exclusively.



audiotape the finest magnetic recording tape you can buy - known the world over for its outstanding performance and fidelity of reproduction. Now available on 1/2-mil, 1-mil and 11/2-mil polyester film base, as well as standard plastic base.



audiodiscs exceed the most exacting requirements for highest quality professional recordings. Avoilable in sizes and types for every disc recording opplica-

audiofilm' magnetically coated standard mation picture film base, provides highest quality synchranized recordings for motion picture and TV sound

To get the most out of your sound recordings, now and as long as you keep them, be sure to put them on Audiotape, Audiodiscs or Audiofilm. THEY SPEAK FOR THEMSELVES.

444 MADISON AVE., NEW YORK 22, N. Y.


IN HOLLYWOOD: 1006 N. Fairfax Ave. IN CHICAGO: 6571 N. Olmsted Ave. Export Dept.: 13 East 40th St., New York 16, N.Y., Cables "ARLAB"

audio record

Published by AUDIO DEVICES, INC. 444 MADISON AVENUE, N. Y. 22, N. Y.

audiodises audiotape audiofilm audiopoints





## QUICK FACTS ON MAGNETIC TAPE RECORDERS

(Additional Information can be obtained by writing to the manufacturer)

Monufocturer	Model and Price	Frequency Response	Dota
	Madel 612 Stereophonic Tape Phonograph \$395.00 Model 610 Monaural Unit \$359.50	40-15,000 cycles (±2 db) at 7½"/sec.  (on playback of Ampex standard type)	Tape playback unit only, for fine reproduction of single track, dual track, or sterophonic (in-line head) pre-recorded tapes at 7½"/sec. Max. reel size, 7". Flutter and wow, below 0.25%. Two separate amplifiers, one for each track, are used on Model 612.  Prices cover "brunette" furniture cabinet. "Blonde" furniture cabinet, \$10.00 additional.
	Madel 620 Amplifier-Speaker in matching cabinet \$169.50		"brunette" furniture. "Blonde" furniture, \$10.00 additional. Use two 620s with 612 tape phonograph for stereophonic sound system.
	Model 600 Portable Tape Recorder \$545.00	40-15,000 cycles (±4 db) at 7½"/sec. (±2 db 40 to 10,000 cycles)	Portable, professional-type single-track recorder with 71/2" tape speed. Takes up to 7" reels for 30 minutes recording time. Signal-to-noise, over 55 db. Flutter and wow, below 0.25%. Starting and stopping time, less than 1 second. Fast forward and rewind, 90 seconds for 7" reel. Timing accuracy ± 0.2% for 30 minute recording. Separate record and playback amplifiers. Separate erase, record and playback heads. VU meter, independent level controls for microphone and line, phone jack for monitoring input or tape while recording. Weight, 28 lb.
AMPEX ELECTRIC CORPORATION 934 Charter 51. Redwood City,	Madel 300-C Console Tape Recorder \$2046.00	30-15,000 cycles (±2 db) at 15"/sec. 40-15,000 cycles (±4 db) at 7½"/sec. (±2 db 40 to 10,000 cycles)	Professional-type, single-track, dual-speed recorder operating at 15" and 71/2" per sec. Signal-to-noise, over 60 db by NAB standards. Instant start and stop. Flutter and wow, less than 0.1% at 15"/sec. Rewind time, 1 min. for 2400-ft. reel. Timing accuracy, ± 0.2%. Push button controls for start, stop and record—may be remotely operated. Separate long-life, plug-in heads for erase, record and playback. Other features as on Model 350C below. Also available for portable or rack mounting.
California	Model 350-C Consale Tape Recarder \$1315.00	30-15,000 cycles (±2 db) at 15"/sec. 30-15,000 cycles (±4 db) at 7½"/sec. 50-7,500 cycles (±2 db) at 3¾"/sec.	Professional-type single or dual-track recorder with tape speeds of 71/2" and 15" or 33/4" and 71/2". Signal-tonoise, 60 db (single track) or 55 db (dual track). Flutter and wow, less than 0.2% at 15"/sec. Instantaneous starting. Rewind time, 1 min. for 2400 ft. reel. Timing accuracy, ± 0.2%. Push-button controls for start, stop, fast forward and rewind. Independent record and playback systems permit monitoring input or tape during recording or playback. Also available for portable or rack mounting.
	Model 350 Stereophonic Recorders 350-2P, Two-Channel — \$1,953.00 350-3P, Three-Channel — \$2,514.00	(same as for Model 300C above)	Separate recording and playback amplifiers for each channel in multi-channel record and playback heads. Individual meter and control panels for each channel. Recorder unit same as Model 350 machine.
	Model 352-C Tape Repraducer \$935.00	30-15,000 cycles (±2 db) at 15"/sec. 30-15,000 cycles (±4 db) at 7½"/sec. (±2 db 40 to 10,000 cycles)	Console-type reproducing unit for playback of 7½ and 15 ips, full-track or dual-track tapes. Provides up to 2 hours, 8 min. playing time on 10½" reel. Signal-to-noise, over 60 db. Flutter and wow, under 0.2% at 15"/sec. Timing accuracy within ± 3.6 seconds for half-hour program. Instant starting and stopping. Rewind time, one min. for 2400-ft. reel. Push button control, tape-speed equalization and reel-size tension adjustment. No erase or record heads—hence no danger of accidental erasure.
-	Other Equipment:		Model 450-C Continuous Tape Reproducer and Model S-3200 Tape Duplicating Systems. Information on request.
AMPLIFIER CORPORATION OF AMERICA 398 Broadway New York 13,	Model 610-A  Tope 5peed  15/16 i.p.s.  \$275	300-2500 cycles	Completely self-contained, battery-operated portable with spring motor drive. Flutter, ± 0.25% over full 30-min. winding cycle. Dual-track recording provides total of 4 hours playing time on 5" reel. Indicator light signals 30 seconds before motor rewind. Playback through head-phones or external amplifier. Incoming signal can be monitored while recording. Overall dimensions, 11" by 8" by 5". Weight, 12 lb.

## COLORED AUDIOTAPE (on colored plastic base)



Green and blue colored Audiatape, in conjunction with the standard red-brown tape, pravide instant visual identification of recorded selections spliced into a single reel (as shown above) — permit fast and eosy calor cueing and calar cading. Eliminate need far identifying leaders between selections.

Color	Length	Reel	Type No.	List Price Each
	150 ft. 300 ft. 600 ft.	3" Plastic 4" Plastic 5" Plastic	151 G 351 G 651 G	\$ 0.85 1.60 3.50
Green	1200 ft.	7" Plastic	1251 G	5.50
	2500 ft. {	NARTB Hub NARTB 10½" Aluminum Reel	2551 HG 2551 RG	10.00 12.85
	5000 ft. {	NARTB Hub NARTB 14" Aluminum Reel	5051 HG 5051 RG	20.00 26.00
	150 ft. 300 ft. 600 ft.	3" Plastic 4" Plastic 5" Plastic	151 B 351 B 651 B	\$ 0.85 1.60 3.50
Blue	1200 ft.	7" Plastic	1251 B	5.50
Dive	2500 ft. {	NARTB Hub NARTB 10½" Aluminum Reel	2551 HB 2551 RB	10.00 12.85
	5000 ft. {	NARTB Hub NARTB 14" Aluminum Reel	5051 HB 5051 RB	20.00 26.00

#### COLORED AUDIOTAPE REELS (empty reels in individual boxes)

These plastic Audiatape reels, in attractive jewel-tone calars, provide many apportunities far color coding recarded material—as ta tape speed, single ar dual track, subject matter, etc.

D. I		TYPE NO.				
Reel	Red	Yellow	Green	Blue	Each	
5" Empty Plastic Reel	5 PBR	5 PBY	5 PBG	5 PBB	\$0.55	
7" Empty Plastic Reel	7 PBR	7 PBY	7 PBG	7 PBB	0.85	

### EMPTY AUDIOTAPE REELS (clear plastic and aluminum)



Standard tape reels in sturdy individual boxes far convenient handling and storage. Box for 10½" and 14" reels has special folding inner sleeve af strong corrugated baard far added safety in handling and storage.

Reel	Type No.	List Price Each
3" Clear Plastic Reel, in Box	3 PB	\$ 0.25
4" Clear Plastic Reel, in Box	4 PB	0.40
5" Clear Plastic Reel, in Box	5 PB	0.55
7" Clear Plastic Reel, in Box	7 PB	0.85
101/2" NARTB Aluminum Reel, in Box	10 RB	4.50
Pair of 101/2" Aluminum Side Flanges, with Screws	10 S	3.35
14" NARTB Aluminum Reel, in Box	14 RB	8.70
Pair of 14" Aluminum Side Flanges, with Screws	14 S	7.25
NARTB Aluminum Hub (Without Box)	10 H	0.65

### CORRUGATED MAILING BOXES (strong, re-usable containers)



Ideal for tape "carrespondence groups" or wherever frequent mailing of recarded material is required.

Size	Type No.	List Price Each
For 5" Reels .	5 M	\$ 0.15
For 7" Reels	7 M	0.20
For 10½" Reels	10 M	0.30
	ŀ	' I



# THE COMPLETE audiotape LINE

#### PLASTIC BASE AUDIOTAPE

The finest, professional-quality tope obtainable - especially formulated to provide the balanced performance which is essential to the most faithful reproduction of the original live sound throughout the entire audible frequency range. Assures maximum fidelity, uniformity, frequency response and freedom from noise and distortion.

Length	Reel	Type Na. ‡	List Price Each
150 ft.	3" Plastic	151	\$ 0.85
300 ft.	4" Plastic	351	1.60
600 ft.	5" Plostic	651	3.50
1200 ft.	7" Plastic	1251	5.50
	NARTB Hub	2551 H	10.00
2500 ft.	NARTB 101/2" Aluminum Reel	2551 R	12.85
	NARTB Hub	5051 H	20.00
5000 ft.	NARTB 14" Aluminum Reel	5051 R	26.00

AUDIOTAPE on 1 mil "Mylar"

Provides 50% more recording time on a single reel of tape. Same super-quality magnetic oxides os Plastic Base Audiotape, but uses base material of 1 mil "Mylar" polyester film having much higher tensile and tear strength than cellulose acetate of the same thickness.

Length	Reel	Type Na. ‡	List Price Each
225 ft.	3" Plastic, in Self-Mailer Box	261	\$ 1.10
900 ft.	5" Plastic	961	4.40
1800 ft.	7" Plastic	1861	7.95
	NARTB Hub	3661 H	16.00
3600 ft.	NARTB 101/2" Aluminum Reel	3661 R	17.95

# AUDIOTAPE ON MYIAT\* POLYESTER FILM

High-strength, super-durable magnetic recording tape that meets the highest professional standards of performance. Made on polyester film, it withstands extreme temperatures, is virtually immune to humidity, and gives maximum tope life under any conditions of use or storage. Available in three base thicknesses to meet individual recording requirement for various applications.

Thickness of Base	Length	Reel	Type No. ‡	List Price Each
	300 ft.	4" Plastic	361	\$ 2.20
	600 ft.	5" Plastic	661	4.25
1 Mil	1200 ft.	7" Plastic	1261	6.85
	2500 (4	NARTB Hub	2561 H	12.50
	2500 ft.	NARTB 10½" Reel	2561 R	15.35
	300 ft.	4" Plastic	371	2.75
1½ Mil	600 ft.	5" Plastic	671	5.00
(standard)	1200 ft.	7" Plastic	1271	8.25
		NARTB Hub	2571 H	15.00
	2500 ft.	NARTB 10½" Reel	2571 R	17.85
	500 ft.	5" Plastic	581	5.00
	1000 ft.	7" Plastic	1081	8.25
2 Mil	0000 1	NARTB Hub	2081 H	15.00
	2000 ft.	NARTB 10½" Reel	2081 R	17.85

t Type Numbers listed cover red oxide tope wound on reel with OXIDE FACING IN. Tope wound with Oxide Out can be supplied if desired, and is identified by the same Type Number except that the last digit is changed from "1" to "0".

Monufacturer	Mode	l and Price			Frequency Response	Doto
	610 "Magnemite"	610-B 610-C 610-TD 610-5D 610-E	Speed in/sec.   17/8   33/4   71/2   71/2   15	\$225 255 275 295 335	100- 3,000 cps 50- 5,000 cps 50- 7,500 cps 50- 7,500 cps 50-15,000 cps	Completely self-contained, battery-operated portables with spring motor drive. Models 610 B, C and TD are dual track; others, single track. Winding interval, 3 to 15 min., depending on tape speed. Motor can be re wound while operating. Indicator light signals 30 sec onds before rewind. Playback through headphones or external amplifier. Incoming signal can be monitored while recording. Overall dimensions, 11" by 8" by 5" for 610 B; 11" by 10" by 7" for all others. Weight 10 to 15 lb.
AMPLIFIER CORPORATION	4-Speed	510-EM	15 7½ 3¾ 1%	395	50-15,000 cps	Completely self-contained, battery-operated portables with spring motor drive. Model 610-DM is single or dual track; Model 610-EM, single track. Speed change with automatic equalization, is by changing capstans Winding interval, 3 to 6 minutes. Motor can be re-
OF AMERICA 398 Broadway New York 13, N. Y.	"Magnemite"	610-DM	7½ 3¾ 1% 15/16	355	50- 7,500 cps	wound while operating. Indicator light signals 30 seconds before rewind. Playback through headphones of external amplifier. Incoming signal can be monitored while recording. Overall dimensions, 11" by 10" by 7". Weight, 15 lb.
		610-DEV	15 7½	445	50-15,000 cps	Operating features of VU "Magnemite" same as above
(athering date	Multiple-Speed VU	610-CDV	3 3/4	405	50- 7,500 cps	except that built in VU meter is provided to measure recording level, output level and "A" and "B" bat
(other modets available)	"Magnemite"	610-BCV	3 <sup>3</sup> / <sub>4</sub> 1 <sup>7</sup> / <sub>8</sub>	365	50- 5,000 cps	teries. Calibrated volume control and high impedance microphone jack also included. One, three and four speed models also available.
		610-ABV	17/8	345	100- 3,000 cps	speed models also available.
		"Flyweight Mognemite" 310-A 310-B 310-C 310-TD 310-5D 310-E	15/ <sub>16</sub> 17/ <sub>8</sub> 33/ <sub>4</sub> 71/ <sub>2</sub> 71/ <sub>2</sub> 15	340 290 320 340 360 400	300- 2,500 cps 100- 3,000 cps 50- 5,000 cps 50- 7,500 cps 50- 7,500 cps 50-15,000 cps	Portable, battery-operated electric motor driven recorders with single tape speed. Models 310-SD and 310E are single track, others dual track. Net weight only 8 lh. Max. reel size, 5". Rewind time, 2 min Earphone monitor and playback. No erase. PM erase available as optional feature. Powered by 5 replaceable mercury batteries. Dimensions, 5½" x 9" x 12".
	Recorde 210-I	"Secret Recorder" 210-B	1 7/8	349	100- 3,000 cps	Hidden in zipper compartment of briefcase, operates anywhere on dry cell batteries. Hidden microphone and concealed start-stop clasp switch. Dual track, single or 2-speed recorder operates on replaceable batteries Maximum reel size 5". Rewind time, 2 min. Earphone
		210-BC	1 7/8 3 3/4	369	100- 3,000 cps 50- 5,000 cps	playback. No erase. PM erase available as optiona feature. Weight complete, including briefcase, 113/4 lb
		"( M	Ampro Career" odel 745		60-11,000 cycles at 7½"/sec. 70-6,000 cycles at 3¾"/sec.	Portable, dual-track, dual speed recorder with woofer tweeter two-speaker system. Electronic eye recording level indicator. Rewind speed, 120" per second. Fast forward editing button, pause lever. Power output. 5 watts. Telephone type input and output receptacles Weight, 25 lb.
AMPRO CORPORATION 2835 North Western Ave. Chicago 18, III.		Mode	i-Fi Two 5 el 757 el 757†	\$239.95	40-12,500 cycles at 7½"/sec. 40-6,000 cycles at 3¾"/sec.	Portable, dual track, dual speed recorder with or with out built-in radio tuner. Includes "Piano Key" controls, electronic eye recording level indicator, automatic selection locator, and provision for mixing and monitoring live and radio-phono inputs. Flutter and wow, less than 0.5%. Fast forward, 72"/sec. Rewind, 120"/sec. Signal-to-noise, 42 db. Power output, 3.2 watts. Built-in 6" x 9" PM speaker. Input receptacles for microphone, radio-phono, or remote control. Weight, 34 lb.
		Mode ("T")	Ampro "Classic el 757A el 757AT In Model No nates Rodi	:" \$257.50 \$292.00 as. abave	40-12,500 cycles at 7½"/sec. 40-6,000 cycles at 3¾"/sec.	Portable dual-speed, dual track recorder designed for heavy-duty school and institutional use. Case is highly resistant to abuse and includes shock-absorbing rubber runners around the side panels. Also available with built-in radio tuner. Features and performance data same as above.
	Mod. 757B (Blond), Mod	k radio tun	hogony): er	\$279.95 314.45	Same as Model 757	Model 757 (or 757T) recorder enclosed in table-type console with storage space for 45 hours of tape recordings. Incorporates amplifier bypass for playback through external hi-fi system if desired.

Manufacturer	Model and Price	Frequency Response	Dota
BELL & HOWELL COMPANY 7 100 McCormick Rd. Chicogo 45, III.	Bell & Howell "MIRACLE 2000"  Model 300-M (dark mahogany) \$299.50  Model 300-8 (blond mahogany) \$314.50	50-12,000 cycles (±2 db) at 7½"/sec.	Table model dual-track recorder with tape speeds of 71/2" and 33/4" per sec. Three separate motors; for drive capstan, feed reel and take-up reel. Push button controls with safety interlock to prevent accidental erase. Speaker system consists of two 8" "woofers" on opposite sides of case and two electrostatic "tweeters" behind front grille. Each electrostatic speaker is provided with 1000 small apertures which act individually as miniature loud speakers. Power output, 10 watts. Input jack for microphone, radio or phonograph. Simple drop-in threading.  Combination radio-phono-tape recorder units (including the "Miracle 2000") are also available, ranging from approximately \$500 to \$2,000. Information on request.
	Model RT-75 Three-5peed Recorder \$164.95	30-12,000 cycles at 7½"/sec. 30-7,500 cycles at 3¾"/sec. 50-4,500 cycles at 1½"/sec.	Portable dual-track recorder with single-lever speed selector for 7½", 3¾" or 1½" per second. Pushbutton recording switch with safety interlock. Fast forward and rewind. Neon recording level indicator. 6" x 9" oval speaker. Two microphone inputs and one radio-phono input. Outputs for external speaker and external amplifier. Power output, 3.5 watts. Crystal microphone included. Weight, 35 lb.
BELL SOUND SYSTEMS, Inc. Columbus 7, Ohio	Model RT-88 Two-5peed Recorder \$139.95	50-10,000 cycles at 7½"/sec.	Dual-track recorder with tape speeds of 7½" and 3¾" per second. Pushbutton controls for tape speed, record, play, fast forward, rewind and stop. Separate tone and volume controls. Neon recording level indicator. Three-motor operation. Inputs for microphone and radio-phono. Outputs for external loudspeaker and monitor head-phones. Power output, 3.5 watts. Weight, 27 lb.
	Cub-Corder  Model 2260 (7½ and 3¾"/sec.)  Model 2261 (3¾ and 1½"/sec.)  \$224.95	200-6,000 cycles at $7 \frac{1}{2}$ "/sec.	Dual-track, two-speed battery operated portable. Has microphone with built-in monitor playback level, miniature transmitter for playback thru radio without connections to set, and wet cell batteries that can be recharged from car cigarette lighter outlet. Output for external amplifier. Fast forward and rewind, 37"/sec. Includes ceramic microphone, shoulder strap, battery charger cable, battery syringe, one 600-ft. reel of tape and take-up reel. Weight, 127/8 lb.
A	Model TWR-2 Recarder and TWPA-10 mplifier-Speaker Unit, in portable cases \$595.00 complete		Professional type dual-track, two-speed regorder available in portable cases or for custom installation. Signal-to-noise ratio, 55db. Total harmonic distortion, 2% at Zero V.U. Total flutter and wow, less than 0.1% RMS at 15"/sec. Rewind and fast forward, less than 60 sec. for 2500 ft. V.U. meter reads record level, output level, bias current. Monitors from tape or input. Includes 3 heads, with provision for 2 more. Three motor drive. A-B test fader and 2-channel mixer for mike and line inputs. Also available in stereo-monaural and single-track models. Weight, 45 lb. total.
BERLANT ASSOCIATES 4917 West Jefferson Blvd. Los Angeles 16, California	Berlant Series X Recorders  Model BRX-1 \$595.00  Model BAX-1 (Automatic) \$745.00	40-15,000 cycles (±2 db) at 15"/sec.  40-15,000 cycles (±4 db) at 71/2"/sec.	Professional type broadcast recorders with single-track erase and record heads and dual-track playback. Plays both single and dual-track tapes. Automatic model, solenoid operated. Performance data same as for 20/20 series above. Timing accuracy, better than 99.8%. Three motors, including new improved hysteresis synchronous direct drive motor. Two-channel input mixer, tape motion regulator, A-B test fader and provision for five heads. Adjustable bias and simplified cueing and editing. Monitors from tape or input. Also available in consolette and portable units.
	Berlant Stereo-Monaural Recorder Model 5BX-4 \$845.00 Model 5BAX (Automatic) \$995.00		Same as Series X above, except with four heads and two amplifier units for extremely versatile stereophonic and binaural recording. Each machine operates as 2 independent recorders using a common reel of tape with the two channels capable of being operated either separately or in conjunction with each other. Records and plays back single or dual track, monaural or binaural. Channel Integrator (\$19.95) permits sound on sound recording with a single recorder, without erasing previously recorded tracks. Model SBAX unit is solenoid operated.

Manufacturer	Madel and Price	Frequency Response	Data
WILCOX-GAY CORPORATION	Model 5A \$129.95 Model 5M \$149.95 Model 5B \$169.95 Model 5F \$199.95	85- 8,000 cycles 80- 8,500 cycles 80-10,500 cycles 70-10,500 cycles	Portable, dual-track recorders with tape speeds of 71/2' and 33/4" per second. Signal-to-noise ratio, 35 db mini mum. Pushbutton operated with interlock to prevent ac cidental erase. Two neon recording level indicators. Fas forward and rewind, less than 23/4" min. for 1200 ft Inputs for microphone and radio-phono. Output for ex ternal speaker. Crystal microphone included.  Model 5A: 4" round speaker. Weight, 26 lb.  Model 5M: 5" x 7" elliptical speaker. Weight, 28 lb.  Model 5B: One 4" and one 5" x 7" speaker. Visual tape index. Weight, 28 lb.  Model 5F: Two 5" x 7" speakers. Visual tape index. Weight, 35 lb.
Charlotte, Michigon	Recordio "PrestOmatic" Model 5U \$269.95	65,15,000 cycles	Portable dual-track recorder with tape speeds of 7½" and 3¾" per second. Signal-to-noise, 35 db minimum Wow and flutter 0.20% at 7½" per second. Machine features same as for Model 5F above. Includes two 5" x 7" woofers and two electrostatic tweeters, three extension speaker jacks, remote stop-start control and crystal microphone with switch. Playback switch permits using mike while playing or recording or when using set as phono amplifier. Weight, 45 lb.
_	Tape-Disc Recordio Model 4C-10 \$199.95	80-6,000 cycles at 33/4"/sec.	Portable combination tape and disc recording and reproducing unit with 33/4" tape speed and 78 rpm disc speed. Records tape, discs, tape to disc or disc to tape. Weight, 30 lb.

All specifications and performance data on tape recorders listed in this directory are based on information supplied by the manufacturer. Performance data are generally based on average values and individual machines sometimes vary widely from published figures, depending on the amount of quality control exercised in manufacture.

Prices subject to change without notice. Consult manufacturer or local dealer for exact price, as some prices are list and others net.

### TAPE RECORDING ACCESSORIES



#### AUDIO SELF-TIMING LEADER TAPE

A strong, durable leader tape of white plastic material — easily written on with ink or pencil. Spaced markings permit occurate timing of leader intervals.

100 ft., ¼" wide, individually boxed.

Type No. 3L . . . . List Price, \$0.60



1 Roll, ½" x 100", with metal

utility dispenser
1 Roll, 1/2" x 66 ft.

1 Roll, 34" x 66 ft.

# PERMACEL 91 SPLICING TAPE

Especially formulated for splicing magnetic recording tope. Adhesive will not squeeze out, dry up or become brittle.

Type

No.

50 ST

56 ST

75 ST

List

Price

\$0.29

0.76

1.01



#### ADHESIVE REEL LABELS

Provide positive identification of your tapes, right on the reel. Simply press to apply, pull off to remove. Envelope of 30 2" x ½" labels.

Type No. 30 AL . . . . List Price, \$0.25



#### AUDIO HEAD DEMAGNETIZER

Campletely removes all permonent magnetism from recording and reproducing heads in a matter of seconds. Operates an 110 volts, 60 cycles. Individually baxed, with 7 ft. cord and plug.

Type No. 400 . . . . List Price, \$12.00



#### AUDIO HEAD ALIGNING TAPE

Pre-recorded at 2,000, 10,000 and 15,000 cps. at 15" per second, with precisely correct head azimuth alignment. Provides a convenient and highly accurate reference for aligning magnetic recording head. Three hundred ft. an 5" reel, individually boxed, with instructions.

Type No. 200 . . . . . . List Price, \$12.00

Manufacturer	Model and Price	Frequency Response	Data
J. C. WARREN CORPORATION 21 Hanse Ave., Freeport, N. Y.	Warren   Battery   Portable   \$298.00	to 2,500 cycles to 4,000 cycles to 6,000 cycles to 12,000 cycles	Portable dual-track tape recorder with completely self-contained, battery powered tape transport, amplifier and speaker for playback. Wet cell battery life up to five hours, depending on tape speed. Has self-contained battery recharger. May be operated on AC. Rewind speed 10 to 1. Max. reel size, 5". May be operated with door closed. Monitors while recording. Input for microphone and headphone monitoring jack. Crystal microphone included. Accessories: Snap-on legs (\$10.00), Canvas carrying case (\$7.50) and shoulder strap (\$5.00). Weight: 22 pounds. Sizes: 6" x 10" x 15".
WEBSTER- CHICAGO CORPORATION	Webcor Fantasy Portable Model 2614 \$149.95  Table Madel 2615 \$159.95  (Prices \$3 higher an West Coast)	to 7,000 cycles at 3 $\frac{3}{4}$ "/sec. 70-10,000 cycles at 7 $\frac{1}{2}$ "/sec.	Dual-track, dual speed recorders in either portable or table models. Simplified pushbutton operation. Monitor control permits listening while recording. Editing switch, separate volume and tone controls, fast forward and rewind. Two automatic volume recording indicators. Inputs for microphone and radio-phono. Microphone included. Output for external amplifier or speaker. Max. reel size, 7". Portable model available in black or tan. Table model in walnut, mahogany, blonde or beige Plextone.
610 Bloomingdale Ave., Chicago 39,	Webcar Rayol Madel 2611 \$219.95	to 7,000 cycles at 3¾"/sec. to 10,000 cycles at 7½"/sec.	Portable, dual-track recorder with 7½" and 3¾" tape speeds. Two magnetic recording heads—two 4-pole motors—one knob control for record, playback and fast rewind—new tape counter. Electronic eye recording level indicator. Includes built-in 6" speaker and crystal microphone. Inputs for microphone and radio-phono. Output for external speaker. Available in black or tan case.
	Webcar Rayol Coronet Model 2612 \$249.95 (\$5 higher on West Coast)		Similar to above, but in larger case with three speakers for balanced sound dispersion. Two magnetic recording heads (as on Model 2611) permit recording in two directions of tape travel without reel turnover.
	Ekotape Model 240 \$189.50	50-7,000 cycles of 7½"/sec. 50-4,000 cycles of 3¾"/sec.	Portable dual-track recorders with 7½" and 3¾" tape speeds. Fast forward, 15 times tape speed. Fast rewind, 112"/sec. Central control selects tape direction, fast forward, standard forward, rewind and stop. Auxiliary controls for tape speed, play-record, volume, tone control. Can monitor thru speaker while recording. Neon record-
WEBSTER	Model 230 \$219.50	50-8,000 cycles ot 7½"/sec. 50-5,000 cycles at 3¾"/sec.	ing level indicator. Inputs for microphone and radio- phono. Output for external speaker. Crystal mike in- cluded. Model 230 includes socket for plug in of remote start-stop controls, and has 5" x 7" PM speaker. Model 240 has 5" round PM speaker.
CO.  Cocine, Wisconsin	Ekotape Model 220 \$239.50	50-10,000 cycles at 7½"/sec. 50-5,000 cycles at 3¾"/sec.	Portable, dual-track recorder with 7½" and 3¾" tape speeds. Fast forward, 15 times tape speed. Rewind, 112"/sec. Central and auxiliary controls same as above. Includes socket in front of case for manual control (furnished) or for remote stop and start controls. Includes 5" x 7" oval PM woofer and 3" round tweeter. Program selection finder geared for maximum of 1800 ft. tape capacity on 7" reel. Other features same as for models described above.
	Ekotape Model 222 (limed oak) Ekotape Madel 224 (mahogany) \$259.50		Similar to Model 220, except in limed oak or mahogany table cabinet with larger (6" x 9") oval PM woofer and 3" round tweeter.

Manufocturer	Model and Price		Frequency Response	Dato
		Tapak (tape-pack) "Newscaster" itandard Madel \$329.25	100-6,000 cycles	Completely self-contained, walkie-type tape recorder with spring-powered transport mechanism and dry battery am plifier. Standard speed, 7½" per second, convertible to 3¾" per sec. if desired. Adjustable to center or side track Rccords, erases, monitors and plays back through head phone, external amplifier or phone input of radio. Fas rewind. Recording characteristics match studio equipment Standard model has 37 db dynamic range. Custom mode with transistor oscillator, has 55 db range. Fitted cover
BROADCAST EQUIPMENT	P	\$344.25	50-9,000 cycles	holds mike, phone, flashlight: price includes all accessories.
SPECIALTIES CORP. P.O. Box 149 Beacon, N. Y.	Tapak (tape-pack) "No	**************************************	100-6,000 cycles	Same as "Newscaster" in appearance and functions, but includes built-in 4" x 6" speaker and increased amplification for reproduction of self-recorded or pre-recorded tapes to room-size audiences. Standard speed, 7½" per second, convertible to 3¾" per sec. if desired. Record or plays up to 50 minutes on one-mil base tape.
	Bo	Minigraph aftery Operated Pocket Size Unit \$289.50 (Available Dec. 1955)	100-4,000 cycles	Pocket-size, subminiature tape recorder. Records dual track I hour total at 33/4" per second or 2 hours at 17/6 per second. Records, erases, monitors and plays back through earphone or external amplifier. Interlocks prevent accidental erase or "double exposure". Special 4" reelstransferrable to any recorder. DC motor operated from 15-hour mercury batteries. Dynamic range, 37 db. Wristwatch mike available as optional accessory.
COLUMBIA RECORDS, Inc.	\$99.95	cycles at	Portable, dual-track recorder with 7½" per second tape speed. Signal-to-noise ratio, 35 to 40 db. Fast forward and rewind, 1200 ft. in 105 seconds. Automatic erase when recording. Single master control and neon recording level indicator. Includes 5" PM speaker, with jack for auxiliary speaker. Can be used as PA system with on without auxiliary speaker. Wooden cabinet with leather toned plastic covering. Complete with ceramic microphone. Weight, 18½ lb.	
799 Seventh Avenue, New York 19, N. Y.		"Narrator" 100-6,000 cycles  Minigraph Battery Operated Pocket Size Unit \$289.50 cycles  (Available Dec. 1955)  Calumbia Madel 461 \$99.95  Columbia Madel 462 \$149.95  Madel TR 670 \$99.95  Model TR 672 \$119.95	Portable dual-track two speed recorder with 7½" and 3¾" per second tape speeds. Signal-to-noise ratio, 35 to 40 db. Fast forward and rewind, 1200 ft. in 105 seconds. Automatic erase when recording. VU meter for accurate recording level indication. Includes two 5" by 7" oval PM speakers and jack for auxiliary speaker. Can be used as PA system with or without auxiliary speaker. Single master control switch. Wooden cabinet with leather-toned plastic covering. Complete with ceramic microphone. Weight, 23½ lb.	
		TR 670	80-8,500	Portable dual-track recorder with 71/2"/sec. tape speed. Fast forward and rewind, 1200 ft. in 90 seconds. 3-watt amplifier and built-in speaker. Output for external amplifier. Microphone included. Weight, 20 lb.
CRESCENT INDUSTRIES, INC. 5900 W. Teuhy Ave.	100	TR 672	•	Portable dual-track recorder with 71/2" and 33/4" per second tape speeds. Wow and flutter, less than 1/2 of 1%. Inputs for mike and radio-phono. Output for external amplifier. Microphone included. Weight, 22 lb.
Chicaga 31, III.		Model TR 673 \$149.95		Portable dual-track, dual speed recorder with two 6" built-in speakers. Wow and flutter, less than ½ of 1%. Fast forward and rewind, 1200 ft. in 80 seconds. Electronic eye recording level indicator. 3-watt amplifier. Inputs for mike and radio-phono. Outputs for external speaker plus high impedance for external amplifier. Includes ceramic microphone. Weight, 23 lb.

Sept.-Oct., 1955

Manufacturer	Madel and Price	Frequency Response	Data
	Crestwood  Model 304 Portable \$229.50  Model 310 in Walnut Console \$339.50	50-10,000 cycles at 7 ½"/sec.	Portable dual-track recorder with 7½" and 3¾" tape speeds. Takes up to 7" reels. Fast forward and rewind, 20:1 ratio. Power output, 10 watts. Distortion, not over 3% at 5 watts output. Wow and flutter, not over 0.3% at 7½"/sec. Inputs for microphone, radio-phono. Outputs for external speaker and headphone monitor. Touch controls for microphone or radio, record or play, bass response, treble response. Push-pull speed change control. Two-neon-lamp volume indicator. Microphone included. Weight, 31 lb.
DAYSTROM ELECTRIC CORP. 753 Moin St. Poughkeepsie, N. Y.	Crestwood "Hi-Fi" 404 Recorder & Preamp. \$229.50 Amplifier & 5pkr. \$100.00 Recorder, Amplifier & 5pkr. in Walnut Console \$429.50	30-15,000 cycles at $7V_2''/\text{sec.}$	Portable dual-track recorder with 7½" and 3¾" tape speeds. Takes up to 7" reels. Fast forward and rewind, 20:1 ratio. Power output, 10 watts. Distortion, less than 2%. Wow and flutter, not over 0.3% at 7½"/sec. Provision for head alignment. Inputs for microphone, radiophono. Outputs for monitor and power amplifier. Electronic eye recording level indicator. Jack for VU meter. Weight, 28 lb.  Model 402 power amplifier with 10-watt output and 8" speaker weighs 17½ lb. Jack provided for external speaker.
	Crestwood "Concerto" Model 360 \$299.50	50-10,000 cycles at 7 ½"/sec.	Model 304 recorder unit mounted in mahogany or limed oak table consolette, containing two speakers properly baffled for full range music reproduction. Also available with legs for use as an arm chair height console.
De JUR AMSCO CORP. 45th & Northern Blvd., Long Island City, N. Y.	De Jur Model TK820 \$379.50	40-16,000 cycles (±2 db) at 7½"/sec. 50-10,000 cycles (±2 db) at 3¾"/sec.	Portable dual-track recorder with hysteresis synchronous, dual speed reversible motor and push-button track reversal. All functions electronically controlled by piano key switchboard relay operation. Four separate erase and record-playback heads. Illuminated program selector. Electronic eye recording level indicator. Signal-to-noise, 55 db. Flutter and wow, 0.1% at 7½"/sec. Harmonic distortion, 0.8% at full rated output. Power output, 6 watts undistorted. Rewind time, 90 sec. for 1200 ft. either direction. Inputs: 2 high impedance, 1 low impedance. Outputs: 1 high impedance, 1 low impedance. Three PM speakers and 2 electrostatic tweeters. Includes cardioid dynamic mike.
DuKANE CORPORATION 51. Charles,	DuKane "Tru-Fidelity" Recorder  Model 11A200 \$395.00	50-10,000 cycles (±1½ db) at 7½"/sec. 50-7,500	Portable, dual-track, dual-speed recorder with 71/2 watt power output. Signal-to-noise ratio, 50 db on playback, distortion less than 5% at full output. Rewind time, 80 seconds for 7" reel. Fast forward, 100 seconds for 7" reel. Output for auxiliary speaker, monitor headphone and for feeding to input of another recorder for direct tape copying. Inputs for microphone, phonograph, radio. Electronic eye recording level indicator, automatic footage counter and exclusive Room Balance Control. Weight, 39 lb.
	DuKane "Automatic" Model 11A240 \$469.50	cycles (±1½ db) at 3¾"/sec.	Same as Model 11A75 above, but designed for fully automatic sound slidefilm projection in conjunction with DuKane push button filmstrip projector. A 40 cycle signal recorded on the tape changes pictures automatically without any audible cues.
EDUCATIONAL LABORATORIES INC. 1823 Jefferson Place, N. W. Washington 6, D. C.	Educarder Dual Model M-6 \$239.00	70-7,500 cycles at 7½"/sec. 70-5,000 cycles at 3¾"/sec.	A complete portable, two-channel two-speed tape recorder. Each channel has its own amplifier and separate record-reproduce and erase heads. Can be used for binaural recording or playback, or for recording on one channel while listening to the other, permitting two-part recordings, duets, comparison drills, etc. Meter recording indicator, tape-film synchronizer (optional) and many other features.

Manufacturer	Madel and Price	Frequency Response	Data
	Telectro- tape Portable Model 556 \$79.95	flat to about 6500 cycles at 3¾"/sec.	Light-weight, dual-track recorder with 3¾" tape speed Handles up to 5" reels, providing up to 1 hour recording time. Wow and flutter, approximately 0.5%. High impedance microphone input may also be used for radic input. Extremely simple threading and operation. Neon bulb recording level indicator. Weight, 16 lb. Includes crystal microphone with stand. Built-in speaker.
TELECTRO- SONIC CORPORATION 35-18 37th St. Long Island City 1, N. Y.	Telectro- tape Custom 220 \$99.50 (without case)	50-12,000 cycles ( $\pm 3$ db) at 7 $rac{1}{2}$ /sec.	Basic dual speed recorder (7½" and 3¾"/sec.) unit with recording amplifier, playback pre-amp and erase oscillator for custom, table or portable mounting. Signal-to-noise, 45 db. Distortion, less than 2%. Flutter and wow, less than 0.3% RMS. Max. reel size, 7". Electronic eye recording level indicator. Inputs for microphone and radio-phono. Also available: Custom 220P monaural tape player (\$49.50) and Custom 220BMP binaural and monaural tape player. (\$61.50). Tape player prices cover mechanism only.
	Telectro-tape Professional 1000 Two-Unit Portable (Price on request)	30-15,000 cycles (±2 db) at 15"/sec. 30-15,000 cycles (±4 db) at 7½"/sec. 30-10,000 cycles (±2 db) at 7½"/sec.	Professional type two-unit, dual-track portable with 15" and 7½" tape speeds. Signal-to-noise, over 55 db at both speeds. Distortion, less than 2% RMS. Flutter and wow, less than 0.2% at 15"/sec. Starting time, less than 0.1 second. Stopping distance, less than 2" at 15"/sec. Playback timing accuracy, better than 0.2%. Max. reel size, 10½". Pushbutton controls, A-B monitor switch, input selector switch, VU meter switch for playback level, record level, bias and erase current. Output, 600 ohms balanced. Remote control available.
THREE DIMENSION COMPANY  Division of Bell & Howell 3512 N. Kostner Ave., Chicogo 41, III.	TDC "5tereotone" Portable \$229.50	50-10,000 cycles (±2 db) at 7½"/sec.  50-8,000 cycles (±3 db) at 3¾"/sec.	Portable, two-speed dual-track recorder. Vertical design with 10-inch extended range speaker. Three separate motors with electro-magnetic braking and interlocking push-button control. Distortion less than 3% at half output. Signal to noise ratio better than 36 db. Wow and flutter below 0.2% at 7½"/sec. 7-tube amplifier with push-pull output delivers over 8 watts audio. Fast forward and rewind, 1200 feet in 40 seconds. Program indicator for permanent pin-point referencing. Two output jack for connecting either external amplifier or extension speaker. Prices include controlled reluctance microphone, power cord, radio-phono patch cord, and spare 7" reel. Neon indicators for volume and bass-treble controls. Two position speaker. Can be used as public address. Record safety lock. Controls: stop, forward, rewind, play, speaker, record.
VIKING OF MINNEAPOLIS 3520 E. 43rd 5t. Minneapolis 6, Minn.	Viking Full Fidelity 75 Tape Deck  FF75 Monaural Playback Unit FF75B Binaural Playback Unit FF75R Monaural Record-Playback Unit \$67.45	40-14,000 cycles at 7½"/sec. (depending on amplifier)	Tape Playback and Record-Playback units for custom installation in hi-fi systems. Tape speed, 71/2"/sec., with belt change for 33/4"/sec. Signal-to-noise, 45 db or more. Flutter, 0.2% or less. Maximum reel size, 7". Total harmonic distortion, less than 1.0% with NARTB compensated preamplifier and NARTB recorded tape. Also available with tapelifter and pressure pad. Weight, basic unit, 9 lb.  Viking matched PB60 playback preamplifier—\$24.50.  Viking matched RP61 record-playback amplifier also available—\$74.50.  Portable carrying case for FF75R and RP61—\$19.95.
V-M CORPORATION Benton Harbor, Michigan	"tape-o-matic" Model 700 \$179.95	70-15,000 cycles (±5 db) at 7½"/sec.	Portable two-speed, dual-track recorder with push-button controls and two speakers — one "woofer" and one "tweeter". Flutter and wow, less than 0.5% Concealed 60-cycle hum control and bass boost. Includes tape index timer, record-ready light, "distort" light, tape-speed button, treble and bass control, monitor switch, "pause" button for silent momentary stops, safety interlock to prevent accidental erase. Inputs for microphone, radio-phono jack, radio "patch cord", and magnetic phono jack. Output jacks for external speaker and external plus internal speakers.

Manufacturer	Model and Price	Frequency Response	Data
	Model R-5 \$1,575.00	50-15,000 cycles (±1 db) at 15"/sec.	Portable, professional-type, single-track recorder with tape speeds of 7½ and 15" (or 3¾ and 7½") per sec. Signal to-noise ratio, over 60 db. Separate record and playback heads and amplifiers with independent monitor amplifier and speaker.
THE STANCIL- HOFFMAN CORP.  921 North Highland Ave., Hollywood 38, Cal.	Madel 56 Synchronous Magnetic Film Recorder \$1,500.00	45-10,000 cycles (±2 db) 16mm ond 17.5mm film	Synchronous magnetic film equipment for motion picture and TV sound recording. Designed for 24 volt battery operation, 110 volt single phase or 220 volt 3 phase. The equipment is very lightweight and housed in small lightweight cases for casy portability.  Signal-to-noise: at least 55 db.  Maximum harmonic distortion: 1.5% from full level.  Film capacity: 1000 feet.
	Model CRM-15 Multi-Channel Communications Recorder  (Prices on Request)	200-7,500 cycles ( $\pm 3$ db) at $7\frac{1}{2}$ "/sec.  200-3,500 cycles ( $\pm 3$ db) at $3\frac{1}{4}$ "/sec.	Provides up to 15 simultaneous recording channels on 0.7" wide tape. Recording time, up to 4½ hours for 5,000 foot reel. Two units, with automatic sequence control permit continuous, 24-hour recording. Signal-to-noise, at least 40 db. Distortion, not more than 5% total harmonic at "0" input level. Negligible crosstalk between channels. Push-button control. Fast forward and rewind. Automatic stop.
	TRI-FY "Dixie-Land" Model 110 \$129.95	50-7,500 cycles of 7½"/sec. 70-4,500 cycles of 3¾4"/sec.	Portable, dual-track, two-speed tape recorder with replaceable plug-in type record-playback head. Signal-to-noise ratio, over 40 db. Flutter and wow, less than 0.5%. Fast forward and rewind, 15 to 1 ratio. Tape Guide slotting for perfect tape alignment. Inputs for microphone and radio-phono. Output for external speaker and monitor headphones. Includes 5" speaker and microphone. Foot control optional. Weight, 24 lb.
TAPE RECORDERS, INC. ISO1 W. Congress Street, Chicago 7, III.	TRI-FY "Continental" Model 220 \$189.95	50-8,500 cycles at 7½"/sec. 50-5,000 cycles at 3¾"/sec.	Portable dual track, dual speed recorder with built-in 6-tube AM radio. Mixer circuit permits simultaneous recording from microphone and radio. Signal-to-noise, over 45 db. Flutter and wow, less than 0.5%. Fast forward and rewind, 15 to 1 ratio. Neon bulb recording level indicator. Plugrin record-reproduce head assembly with tape guide slotting. Inputs for mike and external radio-phono. Outputs for external speaker and headphones. Weight, 29 lb.
	TRI-FY "Carousel" tape player and recorder Madel 330 \$239.95	50-12,000 cycles at 7½"/sec. 50-6,000 cycles at 3³4"/sec.	Compact dual-track recorder with infinitely variable tape speeds from 3" to 8" per second. Reverses track automatically at end of reel. Provides up to 8 hours nonrepeat programming on 10½" reel without adapter. Flutter and wow, less than 0.3%. Fast forward and rewind. Neon bulb recording level indicator. Inputs for high or low impedance mike and radio-phono. Outputs for external speaker, hi-fi amplifier, VU meter and monitor headphones. Weight, 21 lb.

Manufacturer	Model and Price	Frequency Response	Data
EDUCATIONAL LABORATORIES INC. 1823 Jefferson Place, N. W. Washington 6,	Educorder Duol Model M-7 \$295.00	70-8,000 cycles at 7½"/sec. 70-5,000 cycles at 3¾"/sec.	A higher power output model (nearly 5 watts per channel) the M·7 features a well-known pushbutton tape mechanism, improved frequency response and extremely compact design, in addition to all the above interesting operational possibilities of a complete two channel ape recorde with independent control of each channel. Matchin speaker case available (two 12" speakers, for binaural ocombined playback).
D. C.	Educorder Duol Model M-8 \$389.00	50-12,00 cycles at 7½"/sec. 50-7,500 cycles at 3¾"/sec.	A professional quality model with performance on each channel close to NARTB standards and over 5 watt audio power per channel. Three motor tape drive, positive drag and braking, no pressure pads. VU meter.
ELECTRONIC TEACHING LABORATORIES	Electro-Dual Binaural Portable Model E-2 \$495.00	40-8,000 cycles (±2 db) at 3 <sup>3</sup> / <sub>4</sub> "/sec.	Portable dual parallel track recorder with two separate recording and reproducing channels. Modified binaura circuit permits recording on one channel while listening to pre-recorded teaching material on parallel channel Outputs for binaural or standard headphones. Safety feature prevents erasure of pre-recorded tapes. Safety inter lock coupled to drive when either amplifier is in Record position. Includes provision for head azimuth alignment Separate recording level meters for each channel. Size 23" x 11" x 6". Weight, 29 lb.
1818 M Street Northwest, Washington 6, D. C.	Audio-Visual Electro-Dual Binaural Portable  Model E-2AV \$630.00	40-8,000 cycles (±2 db) at 3 <sup>3</sup> / <sub>4</sub> "/sec.	Consists of standard Electro-Dual E-2 with Electro Synchronizer to match, automatic film strip projector and associated connectors. Designed to play back sound track and automatically advance film strip or (alternatively) slide projection. Electro-Synchronizer has 4 watt auxiliary power amplifier. Model G Electro-Synchronizer can be used for same purpose with any other recorder without synchronized signal being necessary.
	Electro-Duol Binaurol Languoge Labaratory Console, Model E-2CL \$575.00	(as above)	Model E-2 recorder in collapsible portable booth-type console wired for external audio and power supply. Elimi nates under-floor wiring. Any console may serve as master signal source.
	Memocorder \$365.00	100-6,000 cycles of 33/4"/sec.	The MEMO line is intended for the clinical psychiatrist and psychologist, for voice recording and reproduction. Portable unit for out-of-office interviews. Maximum simplicity of threading and operation. Record amplifier includes automatic volume compressor. Unnecessary for operator to set or adjust volume level. Single track recording with cueing channel for other track. Remote pushbutton control for cueing. Maximum reel size, 7".
ELECTRO- SONIC SPECIALTIES 7230 Clinton Rd. Upper Darby, Pa.	Memotope \$405.00	100-6,000 cycles at 3 <sup>3</sup> /4"/sec.	Heavy duty professional recorder designed for rack mounting. Same basic simplicity of threading and operation as portable Memocorder above. Includes remote starting, stopping and cueing controlled from consultation room. Automatic gain control—good recordings at any speech level. Separate head for monitoring from tape while recording. Low impedance input for long microphone lines. Maximum reel size, 7".
	Memograf \$700.00	100-6,000 cycles of 3¾"/sec.	Professional transcription machine designed as companion unit to Memotape. One Memograf can serve 6 to 10 Memotapes. Fast shuttle speed and Auto-Que light enable typist to spot and transcribe notes quickly. Pedal control leaves both hands free for typing. All control switches on machine clearly marked as to function. Heads always accessible for cleaning without removal of covers. Ample storage space in console compartments.
	Fidelivox Continuous Tape Reproducer for Bockground Music \$665.00	40-15,000 cycles at $7\frac{1}{2}$ "/sec. 40-7,500 cycles ot $3\frac{3}{4}$ "/sec.	Rack mounted playback unit accommodating up to 14" reels. Signal-to-noise, over 50 db. Three-motor drive. Simple to thread and use. Automatic reversal and shut-off. Data on request.

Sept.-Oct., 1955

Monufacturer	Model and Price	Frequency Response	Data
EMC RECORDINGS CORP.	EMC Tape Players Model 375 \$79.95	100-6,000 cycles at 334"/sec.	Table-model tape playback units with either 71/2" or 33/4" per second tape speed. No provision for recording. No danger of accidental erase. Signal-to-noise; 35 db for Model 375, 38 db for Model 750. Distortion at peak output, less than 5%. Dual track heads play back single or dual track tapes. Output, 4.5 watts. Built-in 5" PM
5t. Paul 6, Minn.	Model 750 \$79.95	80-12,000 cycles at 71/2"/sec.	speaker, with jack for external speaker. Model 750 also includes a high-impedance output. Weight, 15 lb.
FAIRCHILD	Cansole	50-15,000 cycles (±1 db) at 15"/sec.	Professional type, single-track recorder with 15" tape speed (71/2" and 30" models available). Total noise and distortion -64 db (ref. 21/2% dist.). Adjustable bias Speed tolerance, 0.1%. Built-in VU meter and circuichecking. Unit-type, plug-in chassis. Automatic stop instant braking and reversal. Full protection against accidental erase.
RECORDING EQUIPMENT CORP. 154th 5t. and 7th Ave. Whitestone 57,	Console Model "PIC-SYNC" \$4,000.00	50-15,000 cycles (±1 db) at 15"/sec.	Same as model 126 with the addition of lip synchronous operation. Used with motion picture camera and film projector, synchronous sound tracks are made and played back on 1/4" tape, with no interconnecting equipment Automatic Framing, which assures correct cucing of tape and film, available at additional cost. Other applications include Facsimile recording, multi-track, and telemeter ing. with frequency response to 100 KC.
N. Y.	Control Track Generator Model 41 \$125.00		Portable light weight unit for "On Location" picture synchronous sound track recording on 1/4" tape. Used with any portable tape recorder with 15"/sec. tape speed and frequency response good to 14 KC, a control track is simultaneously applied which later becomes the tape speed control when played back on Pic-Sync recorder.
FEDERAL MANUFAC- TURING AND ENGINEERING	FME Model 37-C \$139.95	50-12,000 cycles at 7½"/sec.	Portable dual-track, dual speed recorder operating a 7½" and 3¾" per second. Signal-to-noise, 43 db. Flutter less than 0.5%. Fast forward and rewind, 20-to-1 ratio Safety lock prevents accidental erase. Instand stop leve for editing. Neon recording level indicator. Power output 3 watts. 5" x 7" elliptical PM speaker. Input jack fo microphone or radio-phono. Output jack for externa speaker. Ceramic mike included. Weight, 27 lb.
CORP.  199-217 Steuben St. Brooklyn 5, N. Y.	FME Model 47-A \$159.50  FME Tape Teck (47A in unfinished case) \$149.50	50-7,000 cycles at 33/4"/sec.	Portable dual-track, dual speed recorder. Embodies al features of the Model 37-C above, plus a drum-type automatic reversible counter, monitor and hi-fi jack fo monitoring with earphones while recording or for playing back through an external hi-fi amplifier. Also has improved fast-forward lever for one-hand operation. Includes ce ramic mike and patch cord with built-in resistance network to match recorder. Weight, 27 lb.  Unfinished Tape Deck is for installation in hi-fi setup
INTERNA- TIONAL RADIO AND ELECTRONICS CORPORATION	Crown Crown Crown Imperial \$379.50 \$399.50		Portable, 3-motor, 3-speed recorder-reproducer unit operating at 15", 71/2" and 33/4" per second. Signal-tn noise, 54 db at 15"/sec.; 52 db at 71/2"/sec.; and 44 dl at 33/4"/sec. Flutter and wow, less than 0.12% at 15"/sec Fast forward and rewind, 35 sec. for 1200-ft. reel. Includ 1 phono and 2 microphone inputs; output jacks for 16 8 & 4 ohms, 2 high-level mix input channels: 8" 9 wat speaker. Provides full P.A. facility even while recording Amplifier output, 35 watts peak at less than 4% distortion 15 watts at 1%; 8 watts at 0.5%. Choice of full or half track heads (interchangeable, plug-in type). Deluxe model has electronic eye. Broadcaster model ha VU meter. Imperial model has VU meter and will handle 101/2" reels.
Sauth 17th St. — & Mishawaka Rd. Elkhart, Ind.	"CROWN" LP Recorder \$449.50	40-8,000 cycles (±3 db) at 3 <sup>9</sup> / <sub>4</sub> "/sec.	Same features as Crown Imperial, but designed to accommodate standard 14", 5000 ft. reels. At 334" per second that gives a total, non-stop recording or playback time of 4 hours and 26 minutes — almost 9 hours dual-track Speed reducer (available for all Crown models) gives an additional tape speed of 17/8" per second.

Monufacturer	Model and	Price	Frequency Response	Data
RANGERTONE INC.		"Rangerette"  Partable Model A-2  \$1,500.00 camplete	45-15,000 cycles (±2 db) at 15"/sec. 50-8,000 cycles (±2 db) at 7½"/sec.	FOR SYNCHRONOUS SOUND RECORDING  Professional-type, single-track, dual-speed recorders, with choice of 3¾", 7½", 15" or 30" per second tape speeds Up to 2 hours recording at 7½" per sec, on 14" reel Distortion, less than 2% total harmonic. Maximum signal to-tape noise, 55 db. Double-puck, tight-loop tape drive Peak-to-peak flutter, less than 0.1% at 15"/sec. Rewind speed controllable continuously from 0 to 250"/sec. in
Model R-SC with synchronizer (Price on Request)  (Price on Request)  (Price on Request)	45-15,000 cycles (±2 db) at 15"/sec. 50-8,000 cycles (±2 db) at 71/2"/sec.	both forward and rewind. Meets all N.A.B. adopted standards. Complete monitoring and mixing facilities VU meter, signal indicator and footage counter calibrated in minutes and seconds. Complete tape editing facilities Also available with positive "sprocketless" synchronization for motion picture and TV applications. Weight of Rangerette — 30 lb.  Kits added to other professional recorders for Synchronous Sound Recording for \$295.00.		
		Model T-700D \$212.50 Model TR-800D (with radio) \$265.00	40-14,500 cycles (±3 db) at 7 ½" /sec. 40-7,500 cycles (±3 db) at 3 ¾ "/sec.	Portable dual track recorder available in either single o dual speed. Convenient keyboard control, electrical sole noid operated. Signal to noise ratio over 48 db on dua
	To This	Model T-700 \$225.00 Model TR-800 (with radio) \$277.50	80-8,000 cycles (±3 db) at 3 <sup>3</sup> 4"/sec.	speed machines and 50 db on single. Distortion less that 0.65% on normal levels. Rewind and fast forward speed 170 ips. Flutter and wow less than 0.3%. Two neon lamp for accurate level setting. Precision revolution indecounter, for instant location of recording. Can be op
	السسا	Model T-10 \$235.00 Model TR-20 (with radio) \$287.50	60-15,000 cycles (±3 db) at 7½"/sec.	erated as a PA system. Provision for electrical remote controls.
	Model T-700 B&M \$235.00 Model TR-800 B&M (with radio) \$287.50 Model T-10 B&M \$245.00 Model TR-20 B&M (with radio) \$297.50		as above	Table models (as above) in solid blonde oak or soli Honduras mahogany. Special pressure relief port for ex tended frequency range.
REVERE CAMERA		Model T-1100 \$159.50 Model TR-1200 (with radio) \$209.50	85-7,000 cycles (±3 db) at 3¾"/sec. 75-12,000 cycles (±3 db) at 7½"/sec.	Portable dual track recorder available in either single (3¾ ips.) or dual (3¾ · 7½ ips.) speed. Signal-to-nois ratio over 48 db on either machine. Distortion less that 1½ at normal levels. Rewind and fast forward, 170 ips Flutter less than 0.3%. Single knob control automatically
COMPANY 230 East 21st 5t. Chicago 16, III.	( 6.	Model T-900 \$199.50 Model TR-1000 (with radio) \$249.50	85-7,500 cycles (±3 db) at 3 <sup>3</sup> 4"/sec.	returns to stop when power is turned off. Dual level indicator. Revolution index counter. Instant stop button Two-speed knob can be changed while in any function Rugged fiberglass case. Two speakers. Can be operated as a PA. Weight, 28 lb.
		Model T-100 \$169.50 Model TR-200 (with radio) \$224.50	85-7,500 cycles (±3 db) at 3¾"/sec.	Portable, dual-track recorder available in either 1½ or 3¾ ips. tape speed. Signal-to-noise ratio, over 45 db a either speed. Distortion, less than 1.5%. Rewind and
	2	Model T-500 \$179.50 Model TR-600 (with radio) \$234.50	100-5,000 rapid Two Weig	rapid forward, single knob control, flutter less than 0.3%. Two level recording indicator. 5" x 7" Alnico V speaker Weight, 25 lb.
		Model T-11 \$264.50	40-16,000 cycles ( $\pm 3$ db) at $7 rac{1}{2}$ "/sec.	High fidelity 10½" reel tape recorder for professiona use and custom installations. Guaranteed specifications signal-to-noise, over 50 db, wow and flutter less than 0.2%. Over-all harmonic distortion, 0.65%; inter-modu lation distortion, less than 2%. Features: One volt cathod follower pre-amplifier output. Monitor amplifier with 2½ watt output. Adjustable 70Kc bias-erase oscillator with indicator. Less than ½ second start and stop. Automatic head demagnetizing. Precision revolution tape counter. Electrical remote with automatic drive roller release.

Manufacturer	Model and Price	Frequency Response	Data
	Model SR-27 Complete with A-920 amplifier \$485.00  Model A-920 Amplifier \$324.00	50-15,000 cycles at 15"/sec. 50-10,000 cycles at 7½"/sec.	Professional type two-speed equipment for portable of stationary use. Tape transport mechanism has true three motor drive and separate erase, record and reproducing heads. A-920 amplifier consists of microphone preamp reproduce preamp, power amplifier and power supply Includes twin speakers for playback. Monitors from input or tape while recording. Input for microphone or high impedance bridging. Output; 10 watts at 15 ohms, line level at 500 ohms. Monitor ouput for headphones. Max reel size, 8".
PRESTO RECORDING CORPORATION	Model R-11 Recording Mechanism (in corrying case) \$827.00 Chossis Only \$775.00	50-15,000 cycles at 15"/sec. 50-10,000 cycles at 7 ½"/sec.	Professional type portable tape mechanism with three head assembly: erase — record — reproduce. Brakes and capstan pressure pulley solenoid operated. Dual-speed motor heavy-duty capstan drive unit, with tape reels mounted directly on individual torque motors. Flutter 0.15% at 15"/sec. Signal-to-noise, 55 db. Simplified threading, easy access to heads.
P.O. Box 500, Paramus, New Jersey	Model SR-11 Recording Console \$125.00	50-8,000 cycles at 3 <sup>3</sup> 4"/sec.	Professional console-type unit, consists of R-11 mechanism and 901-A amplifier. 900-A amplifier may be substituted if desired. Tape transport panel and amplifier panel are hinged — every component readily accessible.
	Model PB-17A Tape Reproducing Mechanism \$700.00  Model A-904 Amplifier \$146.00	50-8,000 cycles at 3¾″/sec.	Dual-track reproducing mechanism with 33/4" tape speed and automatic reversal, giving up to 8 hours of continuous music on a 4800-ft. reel. At end of this time, mechanism may be made to recycle or stop. Heavy duty capstan drive unit with individual torque motors for each reel. Signal to-noise, 55 db. Flutter 0.35% at 33/4" speed.
	Continuous Tape Reproducing Console \$996.00		Long-playing tape reproducing unit consisting of PB-17A tape transport mechanism and A-904 Amplifier in console cabinet with dust-protective plastic top. Dynamic range 45 db. Also available with PB-15A mechanism, which is similar to PB-17A except with 10½" reel capacity only
RADIO CORPORATION OF AMERICA	Model 7TR3 Portable \$189.95	70-10,000 cycles at 7½"/sec.  70-5,000 cycles at 3³4"/sec.	Portable, dual-track recorder with tape speeds of 7½ and 3¾"/sec. Push-button controls for play, record, fast forward, rewind and stop. Rewind time, 2 min. for 1200 ft. Normal and overload neon bulbs for recording level Counter for indicating relative tape position. Built-ir microphone well for ceramic mike facilitates use and storage. Voice-music switch for microphone recording Inputs for microphone and radio-phono. Includes 6½ PM woofer and two 3½" PM tweeters. Output jack for external speaker. Power ouput, 2 watts. Max. reel size, 7"
RCA Victor Division Camden 2, N. J.	Model RT-11B Cabinet Rack Mounted \$895.00 Model RT-12C Console \$1070.00	50-15,000 cycles (±2 db) at 15"/sec. 50-10,000 cycles (±2 db) at 7½"/sec.	Professional type, dual-speed tape recording equipmen available in cabinet rack or console mounting. Three sepa rate heads, with automatic tape lift on fast forward or re wind. Automatic "tape break" stop. Local or remote push button control of all functions. Signal-to-noise ratio; 60 dr at 15"/sec., 55 db at 7½"/sec. Wow and flutter combined; 0.1% RMS at 15"/sec., 0.2% at 7½"/sec. Distortion, 3% total RMS harmonic at 400 cycles, reference recording level. Timing accuracy; ±5 seconds in 30 min (machine to machine), ±2½ seconds in 30 min. when played back on same machine at same temperature and humidity. Capstan is synchronous. Start and stop. 0.1 second. Rewind speed, 1 min. for 10½" reel.

Manufacturer	Model and Price	Frequency Response	Data
LIVINGSTON ELECTRONIC CORPORATION Livingston, N. J.	Binaurol- Manourol Tope Ployback Unit \$119.50	20-20,000 cycles (±2 db) at 7 ½"/sec. (when properly equalized)	Attractively styled tape playback unit with 7½" pe second tape speed. Does not record and cannot erast recorded tapes. Arranged for monaural or binaural play back of single or dual track tapes. Rewind time, 75 second for 1200 ft. Amplifier and speaker not included. Outpu level, 5 millivolts from tape recorded at Zero VU. Outpu impedance, 1800 ohms at 1000 cps, variable with fre quency. Max. reel size, 7". Also available without case for custom installation.
	F 35-B "Citation" Model 5 36-B \$370 (in portable cose) (for rock mounting)	F35-B (±2 db) 50-10,000 at 7½" 50- 5,000 at 3¾"  \$36-B (±2 db) 50-15,000 at 15" 50-12,000 at 7½"	Professional type two-speed units for portable, rack of custom mounting. F35-B: 7½" and 3¾"/sec. S/N 45 db half track. S36-B: 15" and 7½"/sec. S/N, 54 df full track. Hysteresis synchronous motor drive. Speed varied by capstan change, Both units have rewind time of 40 sec. for 1200 ft. Control knob interlocked to preven accidental erase. Illuminated VU meter. Monitor jack of front panel. Separate record and playback amplifiers. In puts for microphone and radio phono. Cathode followe output. F35-B includes speaker and ceramic microphone
MAGNECORD INC. 1101 S. Kilbourn Ave. Chicogo 24, III.	Model P60A: (without case) \$390  Model P60B8 (with amplifit and corrying case) \$625	40-15,000 cycles (±2 db) of 15"/sec.	Professional portable or rack mount unit with 7½" and 15" tape speeds. Direct motor capstan drive with torque motor takeup. Pushbutton controls, automatic tape lift and tape break control. Separate erase, record and play back heads. Signal-to-noise, 55 db full track. Flutter and wow 0.2% at 15"/sec. Timing accuracy, ±3 sec. in 30 min Fast forward and rewind, 90 sec. for 2500 ft. Adjustable bias, cueing control, deep slot loading. Amplifier has high impedance and unbalanced bridge inputs. Cathode fol lower unbalanced output. Illuminated 4" VU meter.
	M81-AC \$880 M81-ACC \$975 M90-AC 1375 M90-ACC 1450	M81 Series (±2 db) 50-15,000 at 15" 50-10,000 at 7½"  M90 Series (±2 db) 30-15,000 at 15" 40-12,000 at 7½"	Professional type dual speed units with 3 motor drive M81 series: signal-to-noise, 55 db; flutter and wow less than 0.15% at 15"/sec. M90 series: signal-to-noise, 58 db; flutter and wow less than 0.1% at 15"/sec. Maximum flexibility of remote control. All units have timing accuracy ±3 sec. in 30 min., fast forward and rewind 55 sec for 2500 ft. Pushbutton controls, single or dual track heads. 4" VU meter for bias, record and reproduce level Separate record and playback amplifier. Monitor from tape while recording. Console units have tip-out panels for easy servicing.
MAGNETIC RECORDERS COMPANY 7120 Melrose Ave. Los Angeles 46, Col.	Portable "Reporter"  Standard Model \$199.50  Deluxe Model \$237.50	80-7,000 cycles	Portable, battery operated recorder with spring motor drive. Power for amplifier furnished by dry batteries Spring drive lasts for 7 minutes at 7½"/sec. tape speed Can also be adjusted for 3¾"/sec. tape speed. Can be rewound while recording. Single control — off, playback record. Complete with batteries, microphone, head phone (or speaker) and tape. Standard Model includes provision for headphone playback only. Deluxe Model includes out put amplifier and loudspeaker. Weight, 12 lb. Made in England.
MAGNETIC RECORDING INDUSTRIES			Magnetic Disc dictating and transcribing machines recording on pre-grooved, reusable magnetic discs. Features in clude manual, semi-automatic or fully automatic control automatic error correction, direct disc indexing, instant stop-start, and syllable-controlled backspacing (from mike or foot control). Weight, 12 lb. Fully automatic dictating transcribing unit in portable case also available.
11 East 16th St. New York 3,	Voice-Master Dispatcher \$255	100-4,500 cps	Semi-automotic dictating-transcribing unit
N. Y.	Voice Master Streamliner 165	100-4,500 cps	Manual control dictoting unit
	Voice-Master Componion 199	100-6,000 cps	Fully automatic transcribing unit
	Voice-Master Ordertoker 155	100-4,500 cps	Telephone recording unit

10 AUDIO RECORD

Manufacturer	Madel and Price	Frequency Response	Data
MAGNETIC RECORDING INDUSTRIES  11 Eost 16th 5t. New York 3, N. Y.	"5ynchrotone" Dual Magnetic Recorder Model VM-62-1 \$289.00	to 10,000 cycles at 7½"/sec.	Two independent channels on standard 1/4" tape; each channel with independent recording — playback facility: simultaneous recording on channel 1 and playback of channel 2; simultaneous (binaural) recording on channel 1 and channel 2; facilities for listening optionally to channel 1 or channel 2 or to both channels. Loudspeaker or head-phone listening; two speeds (either 33/4 and 71/2 or 17/8 and 33/4 inches per second); push-button operation of record, listen, fast forward, fast reverse, and stop. Twin neon recording level indicators. Weight, 30 lb.; 110-120 Volts. 60 cycles; 100 Watts.
	Magneticon Add-A-Booth Language Laboratories		Provide combined use of magnetic discs, magnetic tape and phonograph records. Data on request.
MARK SIMPSON MFG. CO. INC.	"MASCO" Model 53 \$250.00  Model 53R (with radio) \$270.00	80-8,500 cycles (±3 db) at 7½"/sec. 80-5,000 cycles (±3 db) at 3¾"/sec.	Portable dual-track, two speed recorder with 5 watts power output. Push button for instant speed change with automatic equalization. Separate take-up and drive motors. Flutter and wow, 0.3%. Monitoring switch for headphone, internal or external speaker. Inputs for microphone and radio-phono. Outputs for external amplifier speaker or telephone line. Motor switch separate from amplifier. Weight: 40 lb. without radio—43 lb. with radio. Records from radio to tape without external connections
32-28 49th 5t., Long Island City 3, N. Y.	"MASCO" Model 500 \$168.50	50-12,000 cycles (±3 db) at 7½"/sec. 50-7,000 cycles (±3 db) at 3¾"/sec.	Portable two-speed, dual track recorder with single shift-knob control of all functions. Signal-to-noise, over 45 db. Wow, less than 0.3%. Power output, 5 watts. Includes standby and monitor switch, two neon recording level indicators, safety record-lock button, 5" x 7" oval speaker, ceramic microphone and patch cord. Inputs for microphone and radio-phono. Outputs for external speaker and external amplifier. Weight, 23 lb.
MITCHELL MANUFAC- TURING COMPANY 2525 Cloybourn Ave. Chicago 14, III.	Mitchell Model 1425 \$139.95	65-10,000 cycles at 7½"/sec.	Portable, dual-track recorder with tape speeds of 7½° and 3¾″ per second. Fast forward and rewind, 90 seconds for 1200 ft. reel. Bias-erase frequency, 50 kc. Power output, 2 watts undistorted, 3 watts maximum. Built-in 6″ speaker. Inputs for microphone and radio-phono. Outputs for external speaker and external amplifier or monitor. Neon recording level indicator. Recording time indicator. Ceramic microphone included. Weight, 22½ lb.
MOHAWK BUSINESS MACHINES CORP. Brooklyn 33, N.Y.	Mohawk "Midgetope" Battery Operated Portoble \$249.50	200-5,000 cycles (±5 db) at 1½"/sec.	Portable, dual-track recorder. Self-contained battery power supply. Battery life 45 hours. Battery life indicator light. Cartridge-loaded (½ hour to a side.) Rewind, manual, two minutes for ½ hour recording. 3 controls: On-Off, Play-Record. and Volume. Wow and flutter, less than 0.7%. Signal-to-noise ratio, 42 db. One microphone input, high impedance (1 my min.). Output for earphone or external amplifier. Tape, ¼", "Mylar" base. Supplied with microphone earphone. butteries. and tape. Accessories available. Size: 8½" x 3½" x 1½". Weight, 3 lb.
OERLIKON TOOL & ARMS CORP. OF AMERICA Business Machines Div. P.O. Box 3049 Asheville, N.C.	Vanguard Dictating and Transcribing Mochine \$392.50	80-8,000 cycles	Magnetic sheet size 8½" x 11", 10 minutes dictation time. Complete combination model including conference recording, telephone recording, foot control start-stop and backspace, earset, microphone with or without playback speaker. The only machine on which an automatic copy of the dictation can be made simply by inserting two sheets at one time. Sheets are erasable and reusable indefinitely. May be folded and mailed or filed away. Equipped with 5" PM speaker.

Sept.-Oct., 1955

Manufacturer	Model and Price	Frequency Response	Data
	Pentron "Clipper" Model RWN \$129.50	50-9,000 cycles at 7½"/sec. 50-5,000 cycles at 3¾"/sec.	Portable two speed, dual-track recorder with Monomatic single slide-knob control for tape speed, record, play, fast forward and rewind. Signal-to-noise, 42 db. Flutter, under 0.5% at 7½"/sec. Power output, 4 watts. Neon bulb recording level indicator. Inputs for microphone and radio-phono. Outputs for auxiliary speaker and amplifier. Microphone included. Also available with single track heads. Weight, 23 lb.
	Pentron "Pocemaker" Model T-90 \$189.50	50-10,500 cycles at 7½"/sec. 50-5,000 cycles at 3¾"/sec.	Portable dual-track, two speed recorder with Unimagic single-lever control for play, record, fast forward and rewind. One knob speed change. Signal-to-noise, 50 db. Flutter, less than 0.3% at 7½" per sec. Fast forward and rewind, 70 seconds for 1200 ft. Power output 5 watts. Electronic eye recording level indicator. Two Alnico V speakers, 1 woofer and 1 tweeter. Automatic index counter. Inputs for microphone and radio-phono. Outputs for external speaker or amplifier. Weight, 27 lb.
	Pentron "Emperor" Model HF-400 \$249.50	40-12,000 cycles of 7½"/sec. 40-6,000 cycles of 3¾"/sec.	Mechanically similar to Model T-90. Has illuminated VU meter and three-speaker sound system with two 6" woofers and separate 4" "roving" tweeter. LC crossover network at 1000 cycles. Power output, 10 watts push-pull. Weight, 33 lb.
THE PENTRON CORPORATION 777 South Tripp Avenue, Chicago 24, III.	Model MP-2 bosic recorder with preamp. \$174.50	50-12,000 cycles ( $\pm 3$ db) of 7 $rac{1}{2}$ "/sec.	Basic tape mcchanism and preamp in portable case, designed for use in hi-fi systems. Tape mechanism has "Unimagic" single lever control, dual track heads with removable pole pieces. Push-pull speed change. Preamplifier provides record-erase bias and necessary audio output to feed amplifier of hi-fi system. VU meter for recording level. Equalization switch for tape speed. Signal-to-noise, 47 db. Inputs for microphone, radio-phono. Components available separately for custom installation.
	Pentron Tape Player Model PB-A2 \$119.50	50-8,000 cycles at 7½"/sec. 50-5,000 cycles at 3¾"/sec.	Portable magnetic tape reproducer, for playback only of any standard 1/4" tape recorded with dual track at 71/2" or 33/4" per second (single-track heads available at slightly higher cost). Flutter less than 0.5%. Fast forward and rewind speed, 20 to 1.  Complete with amplifier and speaker. Weight, 22 lb.
	Pentron "Dynacord"  Model DTM Tape Mechanism \$395.00  Model DS-10 Preamplifier \$90.00  Tape Mechanism Cose, \$40.00 Amplifier Case, \$25.00	40-15,000 cycles (±2 db) at 15"/sec.  40-10,000 cycles (±2 db) at 7½"/sec.	Professional type, dual-speed recorder for rack or portable mounting. Standard speed, $71/2$ " and $15$ "/sec. Also available for $33/4$ " and $71/2$ " speeds. Signal-to-noise, over 55 dh Flutter and wow, under $0.2\%$ at $15$ "/sec. Starting and stopping time, 0.1 second at $15$ "/sec. Playback timing accuracy, $\pm$ 0.2%. Rewind time, less than 60 sec. for 2400 ft. reel. Three separate heads. High inertia, direct capstan drive. Dynamic braking. Push-button controls with automatic cycling for record, fast traverse, play and stop. Erase interlock, automatic stop and instantaneous stop bar. Monitors from input or from tape while recording.
PREMIER ELECTRONIC LABORATORIES 382 Lafayette St. New York 3, N. Y.	"Tapesonic" Model 70-B \$368.50	40-16,000 cycles ( $\pm 3$ db) at 15"/sec. 40-13,000 cycles ( $\pm 3$ db) at $7 \frac{1}{2}$ "/sec.	Portable professional type dual track unit with 4½" VU meter. Three separate heads, permitting instantaneous monitoring from tape while recording. A.B. switch permits comparison between original and recorded program. Push button operation using seven relays and one solenoid. Three speeds. Flutter and wow, 0.1% at 15"/sec.: 0.2% at 7½"/sec.: 0.3% at 3¾"/sec. Mixing channels for mike, radio or phono inputs. Three heavy duty dynamically balanced motors. Fast forward and rewind, less than one Min. for 10½" reel. Electro dynamic brake action and tape tension. D.C. on preamp heaters. Push-pull 12 wattaudio output.